

Advertiser & Invoicing Companies, Brands, and User Mapping

This guide explains how to create **advertiser companies**, **invoicing companies**, and **brands** in Adhese through the Campaign API, and how to **connect (map) users** to those companies and brands.

All endpoints live under the Adhese API and are versioned with a `/v1` prefix. The server base path is `/api`, so a full path looks like `/api/v1/media-partners` and `/v1/user-mapping`.

Key concepts & terminology

In Adhese, an advertiser company and an invoicing company are **the same underlying entity** — **a media partner** — distinguished by the **roles** assigned to it. A single media partner can hold one or more roles at the same time.

You want to create...	What it is in the API	How
An advertiser company	A media partner with the <code>ADVERTISER</code> role	<code>POST /v1/media-partners</code> with <code>"roles": ["ADVERTISER"]</code>
An invoicing company	A media partner with the <code>INVOICE</code> role	<code>POST /v1/media-partners</code> with <code>"roles": ["INVOICE"]</code>
A company that is both	A media partner with both roles	<code>POST /v1/media-partners</code> with <code>"roles": ["ADVERTISER", "INVOICE"]</code>
A brand	A <i>media brand</i> that belongs to a media partner	<code>POST /v1/media-partners/{mediaPartnerId}/brands</code>
A user ↔ company/brand link	A <i>user mapping</i>	<code>POST /v1/user-mapping</code>

Available roles: `ADVERTISER`, `INVOICE`

Note. The read-only endpoints `GET /v1/advertiser-companies` and `GET /v1/brands` expose the same entities from the campaign-booking perspective (used when creating or editing a campaign). Their `id` values are the media-partner and media-brand ids you create below.

Authentication & headers

Every request is authenticated with a **Bearer JWT** and must carry the Keycloak auth header.

Header	Required	Value	Notes
Authorization	Yes	Bearer <jwt>	JWT access token.
Use-Keycloak-Auth	Yes	true	Required on all <code>/v1</code> endpoints.
Content-Type	For <code>POST / DELETE</code> with a body	application/json	—

Example request line and headers:

```
POST /api/v1/media-partners
Authorization: Bearer eyJhbGciOiJSUzI1NiIsInR5cCI6IkpXVCJ9...
Use-Keycloak-Auth: true
Content-Type: application/json
```

Media Partners

Media partners is the overarching term for an advertiser or debtor. Media partners have media brands associated with them.

Create a Media Partner

```
POST /v1/media-partners
```

Creates a media partner (advertiser company, invoicing company, or both, depending on `roles`).

Request body — CreateMediaPartnerRequest

Field	Type	Required	Description
<code>name</code>	string	Yes	Display name of the company.
<code>roles</code>	array of enum	Yes	Any of <code>ADVERTISER</code> , <code>INVOICE</code>
<code>externalKey</code>	string	No	Your own external reference key.
<code>subsystemExternalIds</code>	object (string → string)	No	External ids per subsystem. Example is a CRM or Advendio ID.

Create an advertiser company

```
{
  "name": "Acme Beverages",
  "roles": ["ADVERTISER"],
  "externalKey": "acme-bev",
  "subsystemExternalIds": {
    "crm": "CRM-10432"
  }
}
```

Create an invoicing company

```
{
  "name": "Acme Beverages Billing BV",
  "roles": ["INVOICE"],
  "externalKey": "acme-bev-billing"
}
```

Create a company that is both advertiser and invoicing party

```
{
  "name": "Acme Beverages",
  "roles": ["ADVERTISER", "INVOICE"]
}
```

Responses

Status	Meaning
<code>201</code>	Media partner created.
<code>400</code>	Invalid input (e.g. empty `name` or unknown role).
<code>401</code> / <code>403</code>	Not authenticated / not allowed.

Status	Meaning
500	Unexpected failure.

“ The 201 response will return a body including the generated id and all information known about the media partner.

List companies

GET /v1/media-partners?limit=50&offset=0

Parameter	In	Required	Type	Description
limit	query	Yes	integer	Max number of results to return.
offset	query	Yes	integer	Number of results to skip.
search	query	No	string	URL-encoded, case-insensitive match on name.
roles	query	No	array	Filter on the role(s) the media partner has, e.g. `roles=ADVERTISER`.
includeInactive	query	No	boolean	Include deactivated media partners.

Response — array of MediaPartner Schema

```
[
  {
    "id": 4021,
    "name": "Acme Beverages",
    "roles": ["ADVERTISER"],
    "externalKey": "acme-bev",
    "subsystemExternalIds": { "crm": "CRM-10432" },
    "active": true
  }
]
```

Get a single media partner

GET /v1/media-partners/{mediaPartnerId}

Parameter	In	Required	Type	Description
<code>mediaPartnerId</code>	path	Yes	integer	The id of the media partner you want to fetch.

Responses

Status	Meaning
<code>200</code>	Media partner found.
<code>400</code>	Bad request -Invalid input or parameters.
<code>401</code> / <code>403</code>	Not authenticated / not allowed.
<code>404</code>	Media partner not found.

`500` Internal Server Error

Update media partner

PUT /v1/media-partners/{mediaPartnerId}

Parameter	In	Required	Type	Description
<code>mediaPartnerId</code>	path	Yes	integer	The id of the media partner you want to update.

Request body — `UpdateMediaPartnerRequest`

Field	Type	Required	Description
<code>name</code>	string	Yes	Media partner name.
<code>roles</code>	string	No	Media partner role: <code>INVOICE</code> , <code>ADVERTISER</code> , <code>INTERMEDIARY</code> , <code>MEDIA</code> .
<code>subsystemExternalIds</code>	object (string → string)	No	External ids per subsystem.

Response

```
{
  "id": 1,
  "name": "Philips",
  "roles": [
```

```

    "ADVERTISER",
    "INVOICE"
  ],
  "externalKey": null,
  "subsystemExternalIds": {},
  "active": true
}

```

Deactivate a media partner

PATCH /v1/media-partners/{mediaPartnerId}/deactivate

Parameter	In	Required	Type	Description
mediaPartnerId	path	Yes	integer	The id of the media partner you want to deactivate.

Check for deactivation by fetching the media partners and see if the deactivated media partner is removed from the list of media partners.

Responses

Status	Meaning
200	Media partner deactivated.
400	Bad request - Invalid input or parameters.
401 / 403	Not authenticated / not allowed.
404	Resource not found.

500 Internal Server Error

Activate a media partner

PATCH /v1/media-partners/{mediaPartnerId}/activate

Parameter	In	Required	Type	Description
mediaPartnerId	path	Yes	integer	The id of the media partner you want to (re)activate.

Check for activation by fetching the media partners and see if the reactivated media partner is added to the list of media partners.

Responses

Status	Meaning
200	Media partner activated.
400	Bad request - Invalid input or parameters.
401 / 403	Not authenticated / not allowed.
404	Resource not found.

500 Internal Server Error

Create brands

A brand is a **media brand** that belongs to a media partner (typically the advertiser company). A brand can be present in multiple media partners.

Create a brand

POST /v1/media-partners/{mediaPartnerId}/brands

Parameter	In	Required	Type	Description
mediaPartnerId	path	Yes	integer	The media partner (company) the brand belongs to.

Request body — CreateMediaBrandRequest

Field	Type	Required	Description
name	string	Yes	Brand name.
externalKey	string	No	Your own external reference key.
subsystemExternalIds	object (string → string)	No	External ids per subsystem.

```
{
  "name": "Acme Cola",
  "externalKey": "acme-cola",
  "subsystemExternalIds": {}
}
```

Responses

Status	Meaning
201	Media brand created.
400	Invalid input.
401 / 403	Not authenticated / not allowed.
404	Media partner not found.

“ As with companies, 201 will return a body including the generated id and all information known about the brand.

List a company's brands

GET /v1/media-partners/{mediaPartnerId}/brands?limit=50&offset=0

Parameter	In	Required	Type	Description
mediaPartnerId	path	Yes	integer	The media partner.
limit	query	Yes	integer	Max number of results.
offset	query	Yes	integer	Results to skip.
includeInactive	query	No	boolean	Include deactivated brands.
search	query	No	string	URL-encoded, case-insensitive match on name.

Response — array of `MediaBrand Schema`

```
[
  {
    "id": 8801,
    "name": "Acme Cola",
    "externalKey": "acme-cola",
    "subsystemExternalIds": {},
    "active": true
  }
]
```

```
}  
]
```

Get a single brand

GET /v1/media-partners/{mediaPartnerId}/brands/{mediaBrandId}

Parameter	In	Required	Type	Description
mediaPartnerId	path	Yes	integer	The media partner.
mediaBrandId	query	Yes	integer	The media brand.
includeInactive	query	No	boolean	Include deactivated brands.
search	query	No	string	URL-encoded, case-insensitive match on name.

Response - Returns a single `MediaBrand Schema`.

```
{  
  "id": 1,  
  "name": "Evnia",  
  "externalKey": "Evnia",  
  "subsystemExternalIds": {},  
  "active": true  
}
```

Update a brand

PUT /v1/media-partners/{mediaPartnerId}/brands/{mediaBrandId}

Parameter	In	Required	Type	Description
mediaPartnerId	path	Yes	integer	The media partner.
mediaBrandId	query	Yes	integer	The media brand.
subsystemExternalIds	object (string → string)	No	integer	External ids per subsystem. Example is a CRM or Advendio ID.

Response - Returns the updated brand information.

```
{
  "id": 1,
  "name": "Evnia",
  "externalKey": "Evnia",
  "subsystemExternalIds": {
    "subbrandid": "tpvision"
  },
  "active": true
}
```

Deactivate a brand

PATCH /v1/media-partners/{mediaPartnerId}/brands/{mediaBrandId}/deactivate

Parameter	In	Required	Type	Description
<code>mediaPartnerId</code>	path	Yes	integer	The id of the media partner.

`mediaBrandId` path Yes integer The id of the brand you want to deactivate

Check for deactivation by fetching the brands and see if it is removed from the list of brands.

Responses

Status	Meaning
<code>200</code>	Media brand deactivated.
<code>400</code>	Bad request - Invalid input or parameters.
<code>401</code> / <code>403</code>	Not authenticated / not allowed.
<code>404</code>	Resource not found.

`500` Internal Server Error

Activate a brand

PATCH /v1/media-partners/{mediaPartnerId}/brands/{mediaBrandId}/activate

Parameter	In	Required	Type	Description
<code>mediaPartnerId</code>	path	Yes	integer	The id of the media partner.

`mediaBrandId` path Yes integer The id of the brand you want to (re)activate

Check for the brand reactivation by fetching the brands and see if it is added to the list of brands.

Responses

Status	Meaning
200	Media brand activated.
400	Bad request - Invalid input or parameters.
401 / 403	Not authenticated / not allowed.
404	Resource not found.

500 Internal Server Error

Connect users to media partners

A **user mapping** grants a user access to a company/brand combination. Each mapping entry requires an `advertiserCompanyId` **and** a `brandId`; `invoiceCompanyId` is optional.

Create a user mapping

POST /v1/user-mapping

Request body — `CreateUserMappingRequest`

Field	Type	Required	Description
<code>user</code>	string (1-255)	Yes	User identifier (e.g. email or username).
<code>mappings</code>	array of `Mapping Schema`	Yes	At least one mapping entry.

Mapping Schema

Field	Type	Required	Description
<code>advertiserCompanyId</code>	integer (≥ 1)	Yes	The advertiser company to grant access to.
<code>invoiceCompanyId</code>	integer	No	Restrict the mapping to a specific invoicing company.

Field	Type	Required	Description
<code>brandId</code>	integer (≥ 1)	Yes	The brand to grant access to.

```
{
  "user": "jane.doe@partner.example",
  "mappings": [
    {
      "advertiserCompanyId": 4021,
      "invoiceCompanyId": 4022,
      "brandId": 8801
    }
  ]
}
```

Responses

Status	Meaning
<code>201</code>	User mapping created.
<code>400</code>	Invalid input (e.g. missing `advertiserCompanyId` or `brandId`).
<code>401</code> / <code>403</code>	Not authenticated / not allowed.

List users with mappings

```
GET /v1/user-mapping?limit=50&offset=0
```

Parameter	In	Required	Type	Description
<code>limit</code>	query	No	integer	Max results (≤ 100).
<code>offset</code>	query	No	integer	Results to skip.
<code>search</code>	query	No	string	Loose match on user identifier.
<code>advertiserCompanyId</code>	query	No	integer	Only users mapped to this advertiser company.
<code>invoiceCompanyId</code>	query	No	integer	Only users mapped to this invoice company.
<code>brandId</code>	query	No	integer	Only users mapped to this brand.

The response includes a `Record-Count` header with the total number of matches.

Response — array of `UserMapping Schema`

```
[
  { "user": "jane.doe@partner.example", "mappingCount": 3 }
]
```

List a single user's mappings

GET /v1/user-mapping/{user}

Parameter	In	Required	Type	Description
<code>user</code>	path	Yes	string	The user identifier.
<code>limit</code> / <code>offset</code>	query	No	integer	Pagination.
<code>advertiserCompanyId</code>	query	No	integer	Filter by advertiser company.
<code>invoiceCompanyId</code>	query	No	integer	Filter by invoice company.
<code>brandId</code>	query	No	integer	Filter by brand.

Response — array of `Mapping Schema`

```
[
  {
    "advertiserCompanyId": 4021,
    "invoiceCompanyId": 4022,
    "brandId": 8801
  }
]
```

Delete a user mapping

DELETE /v1/user-mapping

Request body — `DeleteUserMappingRequest`

Field	Type	Required	Description
<code>user</code>	string (1-255)	Yes	The user identifier.

Field	Type	Required	Description
<code>advertiserCompanyId</code>	integer (≥ 1)	—	Advertiser company of the mapping to remove.
<code>invoiceCompanyId</code>	integer	—	Invoice company of the mapping to remove.
<code>brandId</code>	integer (≥ 1)	—	Brand of the mapping to remove.

```
{
  "user": "jane.doe@partner.example",
  "advertiserCompanyId": 4021,
  "invoiceCompanyId": 4022,
  "brandId": 8801
}
```

Responds `200` when the mapping is deleted.

End-to-end walkthrough

Create an advertiser company, an invoicing company, and a brand, then give a user access to them.

1. Create the advertiser company

```
POST /v1/media-partners

{
  "name": "Acme Beverages",
  "roles": ["ADVERTISER"],
  "externalKey": "acme-bev"
}
```

The response will give you its id → assume `4021`.

2. Create the invoicing company

```
POST /v1/media-partners

{
  "name": "Acme Beverages Billing BV",
  "roles": ["INVOICE"],
  "externalKey": "acme-bev-billing"
}
```

The response will give you its id → assume `4022`.

3. Create a brand under the advertiser company

```
POST /v1/media-partners/4021/brands
```

```
{
  "name": "Acme Cola",
  "externalKey": "acme-cola"
}
```

The response will give you its id → assume `8801`.

4. Map the user to the company + brand

```
POST /v1/user-mapping
```

```
{
  "user": "jane.doe@partner.example",
  "mappings": [
    { "advertiserCompanyId": 4021, "invoiceCompanyId": 4022, "brandId": 8801 }
  ]
}
```

5. Verify the mapping

```
GET /v1/user-mapping/jane.doe@partner.example
```

```
[
  { "advertiserCompanyId": 4021, "invoiceCompanyId": 4022, "brandId": 8801 }
]
```

Error handling

Errors are returned as an [RFC 7807](#) `ProblemDetail` object.

```
{
  "type": "about:blank",
  "title": "Bad Request",
  "status": 400,
  "detail": "roles must not be empty",
  "instance": "/api/v1/media-partners"
}
```

Status	Meaning
400	Bad Request — invalid input or parameters.
401	Unauthorized — authentication required or invalid token.
403	Forbidden — authenticated but not allowed to access this resource.
404	Not Found — resource not found.
422	Unprocessable Entity — the request was understood but could not be processed.
500	Internal Server Error — unexpected failure.

Schema reference

CreateMediaPartnerRequest · MediaPartner Schema

```
{
  "id": 4021,
  "name": "string",
  "roles": ["ADVERTISER", "INVOICE", "INTERMEDIARY", "MEDIA"],
  "externalKey": "string",
  "subsystemExternalIds": { "subsystem": "externalId" },
  "active": true
}
```

CreateMediaBrandRequest · MediaBrand Schema

```
{
  "id": 8801,
  "name": "string",
  "externalKey": "string",
  "subsystemExternalIds": { "subsystem": "externalId" },
  "active": true
}
```

AdvertiserCompany Schema

```
{
  "id": 4021,
  "name": "string",
  "active": true,
  "externalId": "string",
  "subsystemExternalIds": { "subsystem": "externalId" }
}
```

Brand Schema

```
{ "id": 8801, "name": "string" }
```

CreateUserMappingRequest Schema

```
{  
  "user": "string",  
  "mappings": [  
    { "advertiserCompanyId": 4021, "invoiceCompanyId": 4022, "brandId": 8801 }  
  ]  
}
```

UserMapping Schema

```
{ "user": "string", "mappingCount": 3 }
```

Revision #11

Created 2026-07-01 08:53:20 UTC by Kevin Voortmans

Updated 2026-07-02 13:38:11 UTC by Casper Steuperaert